

ES2

200 IN-LBS, NEMA 4 AND/OR 7

Indelac's ES2 spring return electric actuators are light duty, quarter turn rotary actuators. These high quality, American made actuators have been designed for use as a fail-safe solution in the industrial valve and damper automation industry. They are recommended for applications requiring system protection from unforeseen power failures.



SPECIFICATIONS:

TORQUE	200 In-Lb (22.6 Nm) spring end
CYCLE TIME	10 sec. / 90° electric, 2 sec. / 90° spring
DUTY CYCLE	25%
MOTOR	115Vac ONLY permanent split capacitor with thermal overload protection
CURRENT RATINGS	.38 FL (Full Load) Amps, .75 LR (Lock Rotor) Amps The motor's LR amps must be taken into account when sizing the input power supply and fuses. Slow blow fuses are recommended
MOTOR BRAKE	Power ON
CERTIFICATIONS	None - General Purpose Actuators Designed to meet NEMA 4 Standards with optional NEMA enclosure types 4X, 9 and 7 available
COATING	Thermally bonded polyester powder
INDICATOR	Visual Dome Indicator
Electric	Feedback from limit switches, same as operating voltage
SWITCHES	Snap action SPDT, 15A @ 250Vac
LUBRICATION	Grease Permanent, little or no maintenance required
WEIGHT	22 lb (10 kg)
MOUNTING	Universal
MOUNTING PAD	ISO 5211 F07 & F10 with 17mm star drive
TEMPERATURE	-40F (-40C) to 150F (65.6C), heater & thermostat required 0F and below Optional double heater for application down to -76F (-60C)
MAX. CYCLES	1,900 power OPEN and power CLOSE, spring fail is to be reserved for emergency use only *

* Allowing this actuator to spring fail as a part of normal operation will severely limit the life expectancy of the product and waives the product warranty



ES2

200 IN-LBS, NEMA 4 AND/OR 7

TECHNICAL DRAWING:

