



# SR & SX



## 200 & 300 IN-LBS, NEMA 7

The SR & SX NEMA 7 rotary electric actuators were designed solely for applications within 200 & 300 in-lbs of torque used in hazardous locations. These heavy-duty reversing actuators are used in place of model SD, SR, SDX, and SX when the area used in requires enclosure rating of Class I Groups C & D and Class II Groups E, F, & G div. I and II.

### SPECIFICATIONS:

TORQUE	SR	200 In-Lb (22.6 Nm)
	SX	300 In-Lb (33.9 Nm)
CYCLE TIME	5 Sec./90	12Vdc, 24Vdc, 24Vac, 115Vac & 230Vac
	10 Sec./90	115Vac extended duty motor (75%)
DUTY CYCLE	25% standard on 115Vac and 230Vac 75% standard on 12Vdc, 24Vdc and 24Vac, optional on 115Vac extended duty motor	
MOTOR	Permanent split capacitor (for AC) with thermal overload protection	



CURRENT RATINGS FL= Full Load, LR= Lock Rotor

115 Vac (Std.)		115 Vac Extended Duty		24 Vac		24 Vdc		12 Vdc		208 Vac/1Ph/60Hz		230 Vac/1Ph/60Hz	
FL	LR	FL	LR	FL	LR	FL	LR	FL	LR	FL	LR	FL	LR
0.38	0.75	0.38	0.75	0.70	3.20	0.70	3.20	1.30	4.20	0.28	0.35	0.25	0.35

The motor's LR amps must be taken into account when sizing the input power supply and fuses. Slow blow fuses are recommended

CERTIFICATION	CSA	Master Contract 178618
LOCATION	Hazardous - Class I, Division 1 & 2, Groups C & D; Class II Division 1 & 2, Groups E, F & G	
CANADIAN	CSA C322802 – Valves – Actuators – For Hazardous Locations CAN/CSA – C22.2 No. 139-1982; CAN/CSA – C22.2 No. 25-1966; CAN/CSA- C22.2 No. 30-M1986	
UNITED STATES	Class C322882 - Valves – Actuators – For Hazardous Locations - Certified to US Standards. ANSI/UL 429, Seventh Ed. – 2013; ANSI/UL 1203 Third Ed. - 2000	

CERTIFIED VOLTAGES	12Vdc, 24Vdc & 115Vac	
APPROVED TEMP.	-4F (-20C) to 104F (40C)	
CERTIFIED OPTIONS	Enclosure Type 4, 7 & 9, One, Two or Three Auxiliary Switches, Push Knob Dec clutching Manual Override, Motor Brake for 12Vdc, 24Vdc & 115Vac, all Feedback Potentiometer options, Modulating Controls LRC, VP, VQ, VP0 & VQ0, Visual Position Indication D, DI, D3L, D3T, TX, TX0 & TQ, Additional Conduit Entry, Heater and Heater with Thermostat (For complete list of options, see option grid in catalog page 33)	

COATING Thermally bonded polyester powder

INDICATOR	Visual	Optional
	Electric	Feedback from limit switches, same as operating voltage

SWITCHES Snap action SPDT, 15A @ 250Vac

LUBRICATION Grease Permanent, little or no maintenance required

WEIGHT	Pound	15 (lb)
	Kilogram	4.54 (kg)

# SPECIFICATIONS (CONTINUED):

MOUNTING	Universal
MOUNTING PAD	ISO 5211 F05 with 14mm star drive
TEMPERATURE	-40F (-40C) to 150F (65.6C), heater & thermostat required 0F and below Optional double heater for application up to -76F (-60C)
OVERRIDE	Manual, non-declutching optional Declutching manual override optional DC voltage and 75% duty cycle motor must be declutching

