

# OPTIONS GRID

FOR ALL ACTUATOR SERIES

Indelac Controls, Inc. offers vast selections of optional equipment, making it possible to utilize our electric actuators in nearly any control environment conceivable. Depending on the options selected, multiple options may NOT fit into the actuator enclosure. Call Indelac Sales Team for best fit of options & configurations.

OPTIONS		Electric Quarter-Turn						Spring Return			Safe & Secure Series (SNS)
		R	SD	S	M	L	K	ES2	AS	ASC	
Enclosure	NEMA 4	Std.	Std.	Std.	Std.	Std.	Std.	Std.	Std.	Std.	Std.
	NEMA 4X										
	NEMA 4 HP										
	NEMA 6										
	NEMA 7										
	NEMA 4 & 7										
	NEMA 4X & 7										
Motor Voltage	115 Vac	Std.	Std.	Std.	Std.			Std.	Std.	Std.	
	115 Vac Extended Duty					Std.	Std.				Std.
	24 Vac										
	24 Vdc										
	12 Vdc										
	208 Vac/1Ph/60Hz										
	230 Vac/1Ph/60Hz										
	230 Vac/3Ph										
	460 Vac/3Ph										
	380 Vac/3Ph										
Coating	Polyester Powder	Std.	Std.	Std.	Std.	Std.	Std.	Std.	Std.	Std.	Std.
	Epoxy Coating										
	Anodize										
	Chromium Conversion w/ UV										
Auxiliary Switches	One										
	Two										
	Three										
	Four										
	Double Pole, Double Throw										
Manual Override	Push Knob, NEMA 4										
	Hand Wheel, NEMA 4				Std.	Std.	Std.				Std.
	Push Knob, NEMA 7										
	Hand Wheel, NEMA 7				Std.	Std.	Std.				Std.
Brakes, Power On								Std.	Std.	Std.	
Brakes, Power Off											



# OPTIONS GRID

## FOR ALL ACTUATOR SERIES

OPTIONS		Electric Quarter-Turn						Spring Return			Safe & Secure Series (SNS)
		R	SD	S	M	L	K	ES2	AS	ASC	
Potentiometer	1K, Single Turn, Std.										
	1R, 0-135 Ohm										
	1K, Ten Turn										
	5K, Single Turn										
	10K, Single Turn										
	10K, Single Turn (dual)										
Positioner	4-20mA										
	4-20mA High Res.										
	0-10 Vdc										
	0-135 Ohm										
	MODBUS High Res.										
Speed Control											
Timer											
Multi-Position	Three Position										
	Four Position										
Position Indicator	Dome Style Visual Indicator	Std.	Std.		Std.	Std.	Std.				Std.
	3 Position Dome Style Indicator										
	Light Indication NEMA 4										
	Light Indication NEMA 7										
	4-20mA Transmitter										
	4-20mA Transmitter High Res.										
Power Supply	For TX & T10										
	For TX & T10										
Additional Conduit Entry	1/2 NPT, NEMA 4										
	1/2 NPT, NEMA 7										
	3/4 NPT										
Special Mounting Pad	Metric tapped mounting holes										
	Special bolt pattern or drive										
	Special shaft, Slot										
Mechanical Stop								Std.	Std.	Std.	
Temperature & Condensation Controls	Breather										
	Heater										
	Heater & Thermostat										
	Desiccant Dry Kit										
	Weather Pack Cord										
Multi-Turn	Without Manual Over Ride										
	With Manual Over Ride										
Reversing Contractor	DC motors										
	3Phase motors										
Transformer	3Phase motors										
Torque Sensor	115 Vac						Std.				
Two Wire Control											

